



# Service Caller SC-100



The Service call system speeds up customer service in hospitality by a multitude.

The customer presses the Caller when he is in need of service and his table number will be shown on the digital display in the service area.

Simple programming and wireless installation make the system quick to set up. With its 16 different signals and various volumes and sounds, the tables can also acoustically be distinguished.

This will ensure the shorted waiting time for the guests and an increase in customer satisfaction.

## Special Features:

- ➔ Wireless connection up to 150 m
- ➔ Up to 998 devices
- ➔ 16 different tones
- ➔ Low battery indicator

## Service Caller SC-100

### Technical specifications

#### Receiver (SCR)

<b>Frequency</b>	868MHz / 902MHz - 928MHz
<b>Sensitivity</b>	-105dBm @ 12dB SINAD
<b>Modulation</b>	FSK
<b>Remote Distance</b>	150M (Max at open area)
<b>Display Type</b>	3 of 4 inch 7 segment display
<b>Power Supply</b>	Constant DC 5V/300mA regulated
<b>Power Consumption</b>	Operating is 123mA ± 2mA, Standby 28mA ± 1mA
<b>Operating Temperature</b>	-10 - 55° C
<b>Storage Temperature</b>	-20 - 60° C
<b>Storage Humidity</b>	10% - 90%
<b>Size</b>	370mm (L) x 205mm (W) x 45mm (H)
<b>Others</b>	Status LED indicator

#### Transmitter (SCT)

<b>Frequency</b>	868MHz / 902MHz - 928MHz
<b>RF Power</b>	10mW
<b>Modulation</b>	FSK
<b>Power Supply</b>	2x Alkaline battery (AAA)
<b>Power Consumption</b>	Standby: 20uA; Active 37mA
<b>Battery Life</b>	6000 times
<b>Operating Temperature</b>	-10 - 55° C
<b>Storage Temperature</b>	-20 - 60° C
<b>Storage Humidity</b>	10% - 90%
<b>Size</b>	68mm (D) x 28,5mm (H)
<b>Others</b>	Status LED indicator. Low Battery LED

