



Touch Monitor LM-15



The LM-15 TFT monitor has an impressive resolution of 1024 x 768. Its slim dimensions and elegant design make the LM-15 a popular POS model.

The built-in speakers make this terminal ideal for multimedia applications, too. Its on-screen display simplifies working processes and also contributes to its ease of use.

The adjustable monitor of the LM-15 can be perfectly adjusted for an ideal angle of view, making it extremely practical.

As an additional option, it can also be supplied with a card reader. It is available in a choice of black and light grey.

Special Features:

- ➔ Resolution: 1024 x 768
- ➔ On-screen display
- ➔ Adjustable monitor
- ➔ Optional:
MSR with PS/2,
MSR with USB,
(Both with tracks 1-3)
Photo stand,
Vesa mounting

Touch Monitor LM-15

Technical specifications

LCD Display	15" TFT panel 250 cd/m ² , XGA 1024x768
Housing colour	black or light grey
Display size	304 x 228mm (Horizontal x Vertical)
Pixel Pitch	0.297 x 0.297 (Horizontal x Vertical)
Contrast	250
Response Time	6/17 ms
Display Colours	16M
Touch screen	ELO 5-Wire Resistive (RS232 or USB)
Touch Controller	eGalax
Viewing Angle	L/R 60-60 Grad, U/D 40-60 Grad
Display Mode	640x480 - 1024x768 (60-75 HZ)
Signal Connector	D-Sub 15pin
PC Interface	Video : RGB analogue 0.7V peak to peak Sync : TTL positive or negative
Back Control	Power, left, right, up, down
Power Supply	Input: AC 110-240v, 47-63hz / Output: DC 12v/4A
Speaker	Integrated, 1.5W
Weight	4,5 kg
Operating Temperature	0-40° C
Operating Humidity	20%-85%
Options	MSR on PS/2, MSR on USB, Photo-Stand, Vesa Mounting
EMC Standard	CE, UL, CUL, CB, VCCI, BSMI, FCC, CCC

